

Product Information Sheet

New & Improved DYNA-PURGE[®] M Most versatile & widely used in the Plastics Industry

DYNA-PURGE M is a versatile non-abrasive, non-chemical engineered thermoplastic purging compound, formulated to flow naturally through the barrel and hot runner system of the injection molding machine, as well as extrusion equipment. Two non-melting but softening thermoplastic ingredients scrub, while an exclusive proprietary additive helps to remove any contamination without leaving behind a residue.

Injection - cold and hot runners
Extrusion - profile, sheet, compounding & blow molding
350°F - 600°F (177°C - 315°C)
All
.030 inch or .75 mm
1 to 2 times barrel capacity(actual amount needed depends on machine conditions)

FEATURES & BENEFITS:

- Developed for color changes, resin changes, preventative machine maintenance and before manual cleaning
- Excellent for purging through hot runner systems with a minimum clearance of .030 inch (.75 mm)
- Effective through a wide temperature range 350°F to 600°F(177°C to 315°C)
- Easy to use no process adjustment necessary use at the resident resin processing temperature and RPM speed
- Non-abrasive, non-melting but softening thermoplastic, which thoroughly loosens carbonized and degraded resin, allowing it to be flushed out of the system
- Safe, non-hazardous, with no chemicals ingredients are FDA compliant
- Heat stable recommended during shutdown and start-up
- Low "cost-per-purge" only small quantity needed to be effective
- No mixing required simply use "as is"
- Unlimited shelf life

Dyna-Purge has been the top performing purging compound for over 30 years! Our product line offers superior cleaning and economic value over in-house methods and other commercial purges. We invite you to sample Dyna-Purge at no charge, so you can prove it to yourself.

Please refer to "Suggested Purging Procedures" for processing information and "Grade Selection Guide" regarding additional products.